



WESTMINSTER

INTERNATIONAL LTD

Telephone : +44 (0)1295 756300

Fax : +44 (0)1295 756302

E-Mail : info@wi-ltd.com

Website : www.wi-ltd.com

WG IS6545N X-Ray Baggage & Parcel Scanner



The WG IS6545N X-Ray Hand Baggage & Parcel Scanner has been designed for screening Hand Baggage and Parcels for contraband items.

It has a Tunnel size of W65 cm x W45 cm and Steel Penetration of 39 mm.

An exclusive standard feature, 6 Colour Imaging enables operators to view screened objects in 6 colours, with each colour correlating to a specific range of Atomic Z-Numbers. 6 Colour Imaging enables operators to achieve optimal material identification and improve throughput with more effective screening technology.

Operators can perform a full analysis with the system's sophisticated screening filters, allowing them to reliably identify threats while ensuring high throughput at even the busiest checkpoints.

Featuring the best in compact checkpoint security, providing high-quality images and greater protection for mailrooms, hotels, and other sites requiring advanced threat detection.

All Westminster X-Ray Systems are equipped with Real-Time Diagnostics, a unique feature which allows users to monitor their machine health status to save you valuable time and money. If requested, Westminster will also be able to connect to your system and troubleshoot any issues remotely.

Features

- Auto Image Archiving (150,000)
- Enhanced Material Discrimination
- Picture Perfect Image Analysis
- Real-Time Diagnostics
- TSA Air Cargo Screening Qualified Technology Listed (ACSQTL)

STANDARD FEATURES

- 6 Colour Imaging
- 9 Quadrant Zoom
- Atomic Z-Number Measurement
- Auto Image Archiving (150,000)
- Baggage Counter
- Colour and Black/ White Imaging
- Continuous Scanning
- Continuous Zoom up to 64x
- Geometric Image Distortion Correction
- Heavy Duty Roller Casters
- High Penetration Function
- Image Annotation
- Image Review
- JPEG Conversion
- Material Discrimination
- Multi-Tier Accessibility
- Network Ready
- Operator Training Program (OTP)
- Organic/ Inorganic Imaging
- Picture Perfect
- Print Image Capable
- Pseudo Colour
- Real-Time Image Manipulation
- Real-Time Self Diagnostics
- Reverse Monochrome
- Save Image (RGB)
- Vertical Zoom Panning

OPTIONAL FEATURES

- 24" LCD Monitor
- Custom Paint
- Density Alert
- Dual Monitors (19" or 24" LCD)
- Entry/ Exit Roller Tables (24" and 48" Increments)
- Foot mat Operator Interlock
- Image Analysis Program - LITE (IAP - LITE)
- Image Analysis Program (IAP)
- Larger Heavy-Duty Casters
- Local Language Support
- Polar Kit
- Radiation Meter
- Remote Workstation Configuration
- Screener Assist Software
- Sloped Conveyor
- Test Case
- Threat Image Protection (TIP) Software
- Tropical Kit
- Wireless Barcode Scanning

OPTIONAL GENERATOR UPGRADE

- Upgrade to 180kV Generator
- Penetration: 41 mm Steel Typical, 39 mm Standard

ASTM F792

- Test 1: 40 AWG4
- Test 3: 1 mm Horizontal/Vertical4
- Test 4: 34 mm4

APPLICATIONS

- Airports
- Banks
- Commercial buildings
- Courthouses
- Embassies
- Government buildings
- Military installations
- Prisons
- Ships
- Security checkpoints

SPECIFICATIONS

Operational Penetration & Sensitivity

- Contrast Sensitivity: 24 Visible Levels, 4096 Gray Level
- Spatial Resolution: 1.0 mm Horizontal, 1.0 mm Vertical
- Steel Penetration¹: 39 mm Typical, 37 mm Standard
- Wire Resolution: 41 AWG Typical, 39 AWG Standard

Computer

- Backup: Uninterruptible Power Supply (Computer Operation - 20 Minute)
- Memory: 4 GB RAM
- Platform: Windows® OS
- Processor: Intel® Core i5
- Storage: 500 GB HDD, 120 GB SSD
- Video Card: 1 GB Video Card

Safety / Standards

- Compliant with USFDA, Centre for Devices and Radiation Health Standards for Cabinet X-Ray Systems (21-CFR 1020.40)
- Film Safety: Guaranteed up to ISO 1600 (33DIN)
- Typical radiation leakage is less than 0.1 mR/hr (Leakage less than 0.5 mR/hr permitted by the Federal Standard)
- TSA Approved

Shipping Crated

Crated dimensions: L231.1 cm x W96.5 cm x H65.1 cm - L91.0" x W38" x H65"

- Crated weight: 600 kg (1,323 lbs)

SPECIFICATIONS

X-Ray Generator

- Beam Direction: Diagonally Upward
- Cooling: Sealed Di-Electric Oil Bath with Forced Air
- Detector: 1280 Channels in an L-Shaped Array
- Duty Cycle: 100%, No Warm-Up Procedure Required
- Tube Current: 0.7 mA
- Voltage: 160kV, Operating at 150kV

Environment

- Humidity: Up to 95% Non-Condensing
- Operating Temperature: 0°C - 40°C \ 32°F - 104°F
- Storage Temperature: -20°C - 60°C \ -4°F - 140°F

Video Display

- Display Resolution: 1280 x 1024; 24 Bit/Pixel Colour
- Display Type: Single 19" LCD Colour Monitor

Electrical Connection

- 110VAC±10%, 50/60Hz, 15 Amp Max
- 220VAC ±10%, 50/60Hz, 10 Amp Max

Physical

- Conveyor Capacity: 165 kg (364 lbs) Evenly Distributed Load
- Conveyor Height: 71.9 cm (28.3") from Floor
- Conveyor Speed: 23 cm/s (45 ft/min) Forward or Reverse
- Dimensions: L153.4 cm x W83.7 cm x H130.5 cm L60.4" x W32.9" x H51.4"
- Net Weight: 431 kg (950 lbs)
- Tunnel Opening: W65 cm x H45 cm - W24.4" x H17.7"

